

RICCIUS+SOHN

Regelungstechnik and Gebäudeautomation GmbH
Haynauer Str. 49
12249 Berlin, Deutschland

Tel: 030 77 99 40, Fax: 030 77 99 479
email: postoffice@riccius-sohn.com



28.06.2004

Spare Part List

Name	Type	Function	Temp. Range	Cont.Type	Sensor Type	Clock	Inp.	Output	Output Signal	Available	Possible Exchange
105.010	heating controller	Outside temperature dependent flow temperature control, burner			NTC		3	1W	2pnt.	x	RV 9010.1
105.020	heating controller	Outside temperature dependent flow temperature control, flipper valve/valve		PI	NTC		3	2S	3pnt.	x	RV 9020.1
105.110	heating controller	room and fixed value control, pump/wall mounted hot water maker/burner	+10°C- +30°C		NTC		3	1W	2pnt.		
105.120											
105.121	heating controller	room and fixed value control, flipper valve/valve	+10°C- +30°C	PI	NTC		3	2S	3pnt.	x	RU94.00-010
105.802		multiple use of outside temperature sensor			NTC		1	3 AF			
105.850	additional module	set point module for day and night			NTC						
105.890	additional module	error message module, 4 signals					4	1			
150.891	additional module	error message module in addition to 105.890, 7 signals					7				
105.892	additional module	error message module, 10 signals					10	1			
105.893	additional module	error message module in addition to 105.892, 10 signals					10				
105.912	additional module	additinal module, 2 outputs, 2pnt.						2S	2pnt.		
105.921	additional module	2 outputs, continous for flipper valve/valve		PI				2S	3pnt.		
105.932	additional module	2 outputs continous for actuators for flaps		P				2S			
160.011	heating controller	Outside temperature dependent flow temperature control, burner and wall mounted hot water maker			NTC		3	1S, 1W	2pnt.		
105.111M	ventilation controller	fixed value control of flow or room temperature, burner/pump	-15°C- +20°C		micro sensor		2	1W	2pnt.	x	
105.112M	ventilation controller	fixed value control of flow or room temperature, burner/pump	+5°C- +40°C		micro sensor		2	1W	2pnt.	x	RU96L2
105.114M	domestic hot water controlle	fixed value control of domestic hot water temperature, burner/pump	+40°C- +100°C		micro sensor		2	1W	2pnt.	x	RU94.00-100
105.122M	ventilation controller	fixed value control von flow or room temperature, flipper valve/flap/valve	+5°C- +40°C	PI	micro sensor		2	2S	3pnt.	x	RU96L2
105.124M	domestic hot water controlle	fixed value control von domestic hot water temperature, flipper valve/valve	+40°C- +100°C	PI	micro sensor		2	2S	3pnt.	x	RU94.00-100
105130M	ventilation controller	fixed value control von exhaust or room temperature, flipper valve/flap/valve	+5°C- +40°C	PI	micro sensor		2	2S	3pnt.		RU96L2
105.210M	heating controller/solar contr	temperature difference	0-20K		micro sensor		2	1W	2pnt.	x	RU94.00-101
105.211M	swimming pool controller	fixed value control of swimming pool temp., pump	+10°C- +25°C		micro sensor		3	1W	2pnt.		RU94.00-101
105.411M	additional module	Outside temperature dependent flap control	+0°C- +20°C		micro sensor		2	1			RU96L2
105.413M	additional module	additional module, shifting of set point	+0°C- +20°C		micro sensor		1	1			RU96L2
105.511M	bridge module	room humidity control	50%-90%	PI	micro sensor		3	1			
105.611M	bridge module	fixed value control of exhaust or room temperature	+10°C- +30°C	PI	micro sensor		3	1		x	RU96L2
105.613M	bridge module	cascade controller for room or exhaust temp.	+10°C- +30°C	PI	micro sensor		3	1			RU96L2
105.615M	bridge module	Outside temperature dependent control of the heater	+20°C- +80°C	PI	micro sensor		3	1			RU96L2
105.702M	universal controller	fixed value control	0-100%	PI	0-10V		3	1			
105.803M	additional module	Offer - demand control	-10°C- +10°C		micro sensor		4	3			RU96L2
105.804M	additional module	multiple use of the outside temperature			micro sensor		2	1			
105.805M	additional module	Electronical caretaker	0°C- +25°C		micro sensor		2	1S, 1W	2pnt.		RU5x-9x
105.806M	additional module	Multiplication of a current value, average for 2 values			micro sensor		2				

Name	Type	Function	Temp. Range	Cont.Type	Sensor Type	Clock	Inp.	Output	Output Signal	Available	Possible Exchange
105.807M	additional module	Outside temperature or room temperature dependent flow temperature control, burner and wall mounted hot water maker	-15°C- +20°C		micro sensor		1	1W	2pnt.		RU94.00-010
105.810M	additional module	3pnt./continous converter			3pnt.		2	2	0-10V	x	
105.902.1M	additional module	output module 0-10V for bridge module						1	0-10V		
160.162M	heating controller	Outside temperature dependent flow temperature control, 2- stage burner	+20°C- +80°C	PI	micro sensor		3	2S	2pnt.		RU94.1K-110
160.163M	ventilation controller	Cascade control of exhaust or room temperature, flipper valve/flap/valve	+10°C- +35°C	PI	micro sensor		3	2S	3pnt.	x	RU96L2
160.165M	ventilation controller	Outside temperature dependent control of the heater	+20°C- +80°C	PI	micro sensor		3	2S	3pnt.		RU94..RU96L2
52.820M	additional module	Minimal limitation	-10°C- +50°C		micro sensor		1	1			
52.822M	additional module	Maximal limitation	+40°C- +100°C		micro sensor		1	1			
RV 300 BP	heating controller	controller for 1 burner and 1 pump 230V			Raumthermostat		1	2	2pnt.		RU94.1K-110
RV 300 BP/BZ	heating controller	controller for 1 burner and 1 pump 230V with operating hour meter			Raumthermostat		1	2	2pnt.		RU94.1K-110
RV 300 BP/U	heating controller	controller for 1 burner and 1 pump 230V with clock/timer			Raumthermostat		1	3	2pnt.		RU94.1K-110
RV 300 BP/U/BZ	heating controller	controller for 1 burner and 1 pump 230V with operating hour meter and clock/timer			Raumthermostat		1	3	2pnt.		RU94.1K-110
RV 300 P2	heating controller	controller for 2 pumps 230V			Raumthermostat		2	2	2pnt.		RU94.1K-110
RV 300 P2/U	heating controller	controller for 2 pumps 230V and clock/timer			Raumthermostat		2	3	2pnt.		RU94.1K-110
RV 300 BP2	heating controller	controller for 1 burner and 2 pumps 230V			Raumthermostat		2	3	2pnt.		RU94.1K-110
RV 300 BP2/BZ	heating controller	controller for 1 burner and 2 pumps 230V with operating hour meter			Raumthermostat		2	3	2pnt.		RU94.1K-110
RV 300 BP2/U	heating controller	controller for 1 burner and 2 pumps 230V with clock/timer			Raumthermostat		2	3	2pnt.		RU94.1K-110
RV 300BP2/U/BZ	heating controller	controller for 1 burner and 2 pumps 230V with operating hour meter and clock/timer			Raumthermostat		2	4	2pnt.		RU94.1K-110
RV 681	heating controller	Electonical immersion thermostate	+10°C- +80°C		Thermoschalter		1	1	2pnt.		
RV813	heating controller	continouser room or ficed value temperature controller with actuator for flipper valve	+10°C- +30°C	P	NTC		3	1	3pnt.		RU94.00-010
RV 903	heating controller	Outside temperature dependent flow temperature controller with remote control for valves	+10°C- +30°C	P	NTC		3	1	3pnt.		RU94.00-010
RV 913	heating controller	continouser room or fixed value temperature controller with actuator for valves	+10°C- +30°C	P	NTC		3	1	3pnt.		RU94.00-010
RV 1000B	heating controller	controller for 1 burner					1	1	2pnt.		RU94.1K-110
RV 1000B/BZ	heating controller	controller for 1 burner with operating hour meter					1	1	2pnt.		RU94.1K-110
RV 1000 BP	heating controller	controller for 1 burner and 1 pump 230V					1	1	2pnt.		RU94.1K-110
RV 1000 BP/BZ	heating controller	controller for 1 burner and 1 pump 230V with operating hour meter					1	1	2pnt.		RU94.1K-110
RV 1000 BP/D	heating controller	controller for 1 burner and 1 pump 380V					1	1	2pnt.		RU94.1K-110
RV 1000 BP/ DBZ	heating controller	controller for 1 burner and 1 pump 380V with operating hour meter					1	1	2pnt.		RU94.1K-110
RV 1000 BP/ U	heating controller	controller for 1 burner and 1 pump 230V with clock/timer					1	3	2pnt.		RU94.1K-110
RV 1010	heating controller	Outside temperature dependent 2pnt.- flow temperature control with clock/timer	+10°C- +30°C		NTC		3	1W	2pnt.		RU94.1K-110
RV 1020	heating controller	Outside temperature dependent continous-flow temperature control with clock/timer	+10°C- +30°C	PI	NTC		3	2S	3pnt.		RU94.1K-110
RV 1120	heating controller	continous room temperature controller with clock/timer for flipper valve/valves	+10°C- +30°C	PI	NTC		3	2S	3pnt.		RU94.00-010
RV 2010	heating controller	Outside temperature dependent 2pnt.- flow temperature control with clock/timer for panels	+10°C- +30°C		NTC		3	1W	2pnt.		RU94.1K-110

Name	Type	Function	Temp. Range	Cont.Type	Sensor Type	Clock	Inp.	Output	Output Signal	Available	Possible Exchange
RV 2020	heating controller	Outside temperature dependent continous flow temperature control with clock/timer for panel	+10°C- +30°C	PI	NTC		3	2S	3pnt.		RU94.1K-110
RV 2120	heating controller	continous room temperature controller with clock/timer for flipper valve/valves for panel	+10°C- +30°C	PI	NTC		3	2S	3pnt.		RU94.00-010
RV 2624	universal controller	fixed value control with additional functions	+30°C- +90°C	PI	NTC		3	2S	3pnt.		RU94.00-010
RV 3011	heating controller	Outside temperature dependent 2pnt.- flow temperature control with clock/timer, 1 burner, 1 pump	+10°C- +30°C		NTC		3	1S, 1W	2pnt.		RU94.1K-110
RV 3021	heating controller	Outside temperature dependent continous flow temperature control with clock/timer, 1 burner, 1 pump	+10°C- +30°C	PI	NTC		3	3S	3pnt.		RU94.1K-110
RV 3121	heating controller	continous room temperature control with clock/timer for flipper valve/valves, 1 burner, 1 pump	+10°C- +30°C	PI	NTC		3	3S	3pnt.		RU94.00-010
RV 3900	swimming pool controller	fixed value control of swimming pool temperature, 2 pumps	+10°C- +30°C		Thermostate		1	2S	2pnt.		RU94.00-100
SMI/2 RV 5010	heating controller compact controller	Actuator with pulse generator Outside temperature dependent 2pnt.- flow temperature control, with clock/timer, 2-stage, burner; pump, as desired	+10°C- +30°C		Thermostate NTC	RT5,UW5,RW6	1 3	1S, 1W	2pnt.		RU94.1K-110
RV 5012	compact controller	Outside temperature dependent 2pnt.- flow temperature control with clock/timer, 2-stage, as desired			NTC	RT5,UW5,RW6	3	2S	2pnt.		RU94.00-010
RV 5021	compact controller	Outside temperature dependent continous flow temperature control with clock/timer, flipper valve, pump, with pump logic, summer/winter switch, as desired.	+10°C- +30°C	PI	NTC		3	3S	2pnt./3pnt.		RV 5027
RV 5022	compact controller	Outside temperature dependent optimizing controller with continous flow temperature control with clock/timer, flipper valve, pump, as desired	+10°C- +30°C	PI	NTC		3	3S	2pnt./3pnt.		RU94.00-010
RV 5025	compact controller	Outside temperature dependent continous flow temperature control with clock/timer,flipper valve, pump, as desired.	+10°C- +30°C	PI	NTC	RT5,UW5,RW6	3	3S	3pnt.		RU94.00.-010
RV 5026	compact controller	Outside temperature dependent continous district heating flow temperature control with clock/timer, flipper valve, pump, as desired.	+10°C- +30°C	PI	NTC	RT5,UW5,RW6	4	3S	3pnt.		RU94.00.-010
RV 5027	compact controller	Outside temperature dependent continous flow temperature control with clock/timer, flipper valve, pump, as desired.	+10°C- +30°C	PI	NTC	RT5,UW5,RW6	3	3S	3pnt.	x	
RV 7010.1	compact controller	Outside temperature dependent continous flow temperature control, burner/wall mounted hot water maker, analogue clock/timer	+15°C- +25°C		NTC		2	1S, 1W	2pnt.		RU94.00.-010
RV 7010.R	compact controller	Outside temperature dependent continous flow temperature control, burner/wall mounted hot water maker, analogue quarz clock/timer	+15°C- +25°C		NTC		2	1S, 1W	2pnt.	x	
RV 8020	compact controller	Outside temperature dependent continous flow temperature control with flipper valve actuator with clock/timer, as desired.	+15°C- +25°C	PI	NTC	RT5,UW5,RW6	3		3pnt.	x	
RV 9010	compact controller	Outside temperature dependent 2pnt.- flow temperature control with clock/timer, 1 burner, 1 pump, as desired	+15°C- +25°C		NTC	RT5,UW5,RW6	3	2S	2pnt.	x	
RV 9017	compact controller	Outside temperature dependent 2pnt.- flow temperature control with digital clock/timer and pump logic, 1 burner, 1 pump	+15°C- +25°C		micro sensor		3	2S	2pnt.		RU94.1K-110

Name	Type	Function	Temp. Range	Cont.Type	Sensor Type	Clock	Inp.	Output	Output Signal	Available	Possible Exchange
RV 9020	compact controller	Outside temperature dependent continous flow temperature control with clock/timer, flipper valve/valve, pump, as desired.	+15°C- +25°C		NTC	RT5,UW5,RW6	3	3S	3pnt.	x	
RV 9027	compact controller	Outside temperature dependent continous flow temperature control with digital clock/timer and pump logic, 1 pump, flipper valve/valve	+15°C- +25°C	PI	micro sensor		3	2S	3pnt.		RU94.1K-110
RV 9521	compact controller	Outside temperature dependent continous flow temperature control with digital clock/timer with room sensor, 1 pump, valve, burner	+10°C- +30°C	PI	micro sensor		5	4S	2pnt./3pnt.		RU94.1K-110
RV 9522	compact controller										
RV 9524	compact controller	Outside temperature dependent continous flow temperature control with digital clock/timer also without room sensor, 1 pump, valve, burner	+10°C- +30°C	PI	micro sensor		5	4S	2pnt./3pnt.		RU94.1K-110
RV 9526	compact controller	Outside temperature dependent continous district heating flow temperature control with digital clock/timer with room sensor, 1 pump, valve	+10°C- +30°C	PI	micro sensor		5	4S	2pnt./3pnt.		RU94.1F-110
RU52-xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water , pump, valve	+5°C- +30°C	PI	micro sensor		10	4S	2pnt./3pnt.	x	
RU53-xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		10	5S	2pnt./3pnt.	x	
RU54-xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		13	7S	2pnt./3pnt.	x	
RU55-xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		15	10S	2pnt./3pnt.	x	
RU56-xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		15	15S	2pnt./3pnt.	x	
RU57-xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		15	15S	2pnt./3pnt.	x	
RU84.xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, pump, valve,	+5°C- +30°C	PI	micro sensor		7	4S	2pnt./3pnt.	x	
RU86.xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		7	5S,1W	2pnt./3pnt.	x	
RU94.xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		6	3S,1W	2pnt./3pnt.	x	
RU96.xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		7	5S,1W, 1OC	2pnt./3pnt.	x	

Name	Type	Function	Temp. Range	Cont.Type	Sensor Type	Clock	Inp.	Output	Output Signal	Available	Possible Exchange
RU98.xx-xxx	DDC- heating controller	Outside temperature dependent 2pnt./continous flow temperature control with/without room sensor, domestic hot water, pump, valve, burner/district heating	+5°C- +30°C	PI	micro sensor		6	7S, 1W, 2OC	2pnt./3pnt.	x	
MP19.1K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade	+5°C- +30°C	PI	micro sensor		3	0-10V, 1S	continous/2pnt.		RU98.L2.U
MP19.1-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or Raumtemperatur	+5°C- +30°C	PI	micro sensor		2	0-10V, 1S	continous/2pnt.		RU98.L2.U
MP19.2K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade	+5°C- +30°C	PI	micro sensor		3	3S	2pnt./3pnt.		RU98.L2.U
MP19.2-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature	+5°C- +30°C	PI	micro sensor		2	3S	2pnt./3pnt.		RU98.L2.U
MP19.3K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade	+5°C- +30°C	PI	micro sensor		3	0-20V,1S	continous/2pnt.		RU98.L2.U
MP19.3-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature	+5°C- +30°C	PI	micro sensor		2	0-20V,1S	continous/2pnt.		RU98.L2.U
MP19.4K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade	+5°C- +30°C	PI	micro sensor		3	3S	stage/2pkt		RU98.L2.U
MP19.4-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature	+5°C- +30°C	PI	micro sensor		2	3S	stage/2pnt		RU98.L2.U
MP19.124K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, mixing flap, heater, cooler	+5°C- +30°C	PI	micro sensor		8	0-10V, 7S	continous/2pnt/3pnt	x	RU98.L2.U
MP19.W221K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, heat recovery,heater, cooler	+5°C- +30°C	PI	micro sensor		8	0-10V,7S	continous/2pnt/3pnt		RU98.L2.U
MP19.020K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, heater	+5°C- +30°C	PI	micro sensor		8	3S	2pnt./3pnt.		RU98.L2.U
MP19.S11K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, heater, cooler	+5°C- +30°C	PI	micro sensor		8	0-10V,2S	continous/2pnt.		RU98.L2.U
MP19.W1400-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or Raumtemperatur, heat recovery, heater	+5°C- +30°C	PI	micro sensor		8	0-10V, 3S	continous/2pnt.		RU98.L2.U
MP19.31W2K-L(S)	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, heat recovery mixing flap, heater	+5°C- +30°C	PI	micro sensor		8	0-10V, 5S	continous/2pnt/3pnt		RU98.L2.U

Name	Type	Function	Temp. Range	Cont.Type	Sensor Type	Clock	Inp.	Output	Output Signal	Available	Possible Exchange
MP19.122K-LS	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, mixing flap, heater, cooler	+5°C- +30°C	PI	micro sensor		8	0-10V, 5S	continous/2pnt/3pnt	x	RU98.L2.U
MP19.224K-LS	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, heat recovery, mixing flap, heater	+5°C- +30°C	PI	micro sensor		8	0-10V, 5S	continous/stage/3pnt	x	RU98.L2.U
MP19.W121K-LS	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, heat recovery, heater, cooler	+5°C- +30°C	PI	micro sensor		8	0-10V, 5S	continous/2pnt/3pnt	x	RU98.L2.U
MP19.111K-LS	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for the control of the supply, exhaust air or room temperature with cascade, mixing flap, heater, cooler	+5°C- +30°C	PI	micro sensor		8	0-10V, 5S	continous/stage	x	RU98.L2.U
MP19.1D10B-FS	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for control of the humidity, cooler, damper	+5°C- +30°C	PI	micro sensor		8	0-10V, 5S	continous	x	UPK.L2
MP19.1000-DS	DDC- ventilation controller	ventilation controller for air conditioning or ventilation system for control of pressure	+5°C- +30°C	PI	micro sensor		1	0-10V	continous	x	UPK.L2
MP19.2B00-T	DDC- ventilation controller	Temperature controller for control of the temperature in a hot water storage tank	+15°C- +60°C	PI	micro sensor		2	3S	2pnt./3pnt.	x	RU94.00-101U
MP19.4B00-TS	DDC- ventilation controller	Temperature controller for a system with a multiple-stage heat provider	+15°C- +100°C	PI	micro sensor		4	4S	stage/2pnt	x	RU96.1K/UPK
MP19.1-U(S) T5	DDC- 19" clock/timer clock/timer	1 channel clock/timer Analogue clock/timer with daily program (net synchronisation) without reserve, as a plugin in controllers						1S	2pnt.		RT5
RT5	clock/timer	Analogue clock/timer with daily program (quarz synchronisation) with reserve 150h, as a plugin in controllers						1S	2pnt.	x	
UW5	clock/timer	Analogue clock/timer with weekly program (quarz synchronisation) with reserve 150h, as a plugin in controllers						1S	2pnt.		RT5 rebuilt
RW6	clock/timer	Analogue clock/timer with weekly program (quarz synchronisation) with reserve 380h, 12 switching times, as a plugin in controllers						1S	2pnt.		RW8
RW 6 E	clock/timer	Analogue clock/timer with weekly program (quarz synchronisation) with reserve 380h, 12 switching times, for panel installation						1W	2pnt.		RW8 E
UW6	clock/timer	digital clock/timer with weekly program (quarz synchronisation) with reserve 100h, 56 switching times, as a plugin in controllers						1W	2pnt.	x	RW8
RW7	clock/timer	digital clock/timer with weekly program (quarz synchronisation) with reserve 100d, 6 switching times, as a plugin in controllers						1S	2pnt.	x	RW8
RW7 E	clock/timer	digital clock/timer with weekly program (quarz synchronisation) with reserve 100d, 6 switching times, for panel installation						1W	2pnt.		RW9 E
RW9 E	clock/timer	digital clock/timer with weekly program (quarz synchronisation) with reserve 100d, 6 switching times, for panel installation						1W	2pnt.	x	